

# TEST CERTIFICATE

ST-23-02-23-01

**Product:** Floor covering "Finfloor Durable"

**Producer:** Financiera Maderera S.A. FINSA, Carretera N-550 km 57,  
15890 Santiago de Compostela, A Coruña, Spain

**Order:** Determination of Laminate Flooring Topical Moisture Resistance  
according to NALFA-Method and according to ISO 4760:2022-05

**Test report:** 2722461

**Test results:**  
NALFA-Method

		Result: Wet Swell	Result: Re-dry Swell
Final Thickness Swell	Position 1	0,11	0,00
in mm	Position 2-4	0,09	<b>0,01</b>
Qualitative Rating		2	<b>1</b>
Water Penetration		Not Detected	

Planned requirements by NALFA after 24h water load	
Final Thickness Swell Position 2-4 (Re-dry Swell)	<b>≤ 0,3 mm</b>
Qualitative Rating (Re-Dry Swell)	<b>&lt; 3</b>

Method according to ISO 4760:2022-05

Property	Results	Evaluation according to Working Draft of the Revision of prEN 13329:2022, Table 3
Water resistance according to ISO 4760:2022-5	Qualitative - Recovery Swell Rating Final Average: <b>1</b> Final Average - Recovery Swell of Measuring Position 2 - 4: <b>0,05 mm</b>	Additional Requirements <b>fulfilled</b>

Dresden, 23/02/2023



Head of laboratory




Engineer in charge